



UOP LLC
25 East Algonquin Road
Des Plaines, Illinois 60017-5017, USA

PROJECT SPECIFICATION
Project - 301 SHEET

REV	DATE	BY	APP'D	REV	DATE	BY	APP'D

REV

VESSELS
TEC-300-12 ATTACHMENT 1

SERVICE RECYCLE COMPRESSOR SUCTION DRUM (EXISTING)

ITEM NO V-2203

Design	INT	00.0 kg/cm2(g)	@ 000°C
Conditions at Top	EXT	FULL VACUUM	@ 00°C
Operating Conditions		Metal Temperature(Min)	00°C
			00°C

Radiograph	*
Postweld Heat Treat	*

Material	Corrosion Allowance
*	*

This Vessel is in the Following Service(s):

Hydrogen	-
Hydrofluoric (HF) Acid	-
Hydrofluoric (HF) Acid (with Resid. Elem. Control)	-
Wet Hydrogen Sulfide (H2S)	-
Severe Cyclic	-
Caustic	-
Carbonate	-
Amine	-

Vessel Heads

Top	*
Bottom	*

Accessories Applied by Fabricator

Ladder & Platform Clips	*
Insulation Clips & Rings	YES
Vessel Support	*

Nozzles and Manways

Mark	No	Size Inches	Service
	1	2	OUTLET
	1	VESSEL ID	MANWAY
	1	2	INLET
	1	2	INLET
	1	6	HANDHOLE
	2	1 1/2	LG-LC
	1	3	OUTLET

Class	- *
Facing	- *
Normal Liquid Level	= 000 ABOVE BOTTOM TANGENT
Specific Gravity	= 0.000

REFERENCE:


RECYCLE COMPRESSOR SUCTION DRUM ITEM NO V-2203
ORIGINAL UOP PROJECT NO 6950 (1988)
* CUSTOMER OR FABRICATION DWG NO & REVISION:
DAEKYUNG MACHINERY & ENGINEERING CO, DWG. NO. DV-898-001, REV 4 (1989)

NOTES:

MODIFICATIONS REQUIRED FOR THE NEW SERVICE:
1. REPLACE EXISTING MESH BLANKET WITH NEW 700 ID MESH BLANKET (BY OTHERS) STYLE A: MONEL, AS SHOWN. SEE STD SPEC 3-35 AND SUPPORT PER UOP DWG 3-265.
2. SEE NOTES F, G AND H ON SHEET 2.

LEGEND:

————— NEW OR MODIFIED CONFIGURATION
- - - - - EXISTING CONFIGURATION



Drawings Referred to in this Specification

3-265							
-------	--	--	--	--	--	--	--

TEC-300-12-Vessel Reference 1 - Attachment 1.dgn

NOTE - The information in this document is confidential and the property of UOP LLC and must not be disclosed to others or reproduced in any manner or used for any purpose whatsoever without its written permission.



UOP LLC
25 East Algonquin Road
Des Plaines, Illinois 60017-5017, USA

PROJECT SPECIFICATION
Project - 301 SHEET

REV	DATE	BY	APP'D	REV	DATE	BY	APP'

REV

VESSELS
TEC-300-12 ATTACHMENT 1

SERVICE	NET GAS CHLORIDE TREATER (EXISTING)	ITEM NO	V-2007FB
----------------	-------------------------------------	----------------	----------

Design Conditions at Top	INT 00.0 kg/cm ² (g) @ 00°C	EXT FULL VACUUM @ 00°C	
Operating Conditions	Metal Temperature (Min) 00°C		
Radiograph	*		
Postweld Heat Treat	*		
Material	Corrosion Allowance		
*	*		
This Vessel is in the Following Service(s):			
Hydrogen	-		
Hydrofluoric (HF) Acid	-		
Hydrofluoric (HF) Acid (with Resid. Elem. Control)	-		
Wet Hydrogen Sulfide (H ₂ S)	-		
Severe Cyclic	-		
Caustic	-		
Carbonate	-		
Amine	-		
Vessel Heads			
Top	*		
Bottom	*		
Accessories Applied by Fabricator			
Ladder & Platform Clips	*		
Insulation Clips & Rings	NO		
Vessel Support	*		
Nozzles and Manways			
Mark	No	Size Inches	Service
	1	24	MANWAY
NEW NOZZLE(S)			
AI	1	6	INLET
AM	1	20	MANWAY
CD	1	6	OUTLET / BOTTOM
Class - ASME CL150 (NEW) * (EXISTING)			
Facing - RAISED FACE (NEW) * (EXISTING)			
Normal Liquid Level = N/A			
Specific Gravity = N/A			

REFERENCE:

NET GAS CHLORIDE TREATER ITEM NO V-2007FB (FORMERLY ITEM NO.2007F) NOT AN ORIGINAL UOP VESSEL DESIGN.
* CUSTOMER OR FABRICATION DWG NO & REVISION:
PROCON (GB) LTD., DWG NO 457-A11, REV 3 (1989)


NOTES:

MODIFICATIONS REQUIRED FOR THE NEW SERVICE:

- 1) VENDOR DRAWING INDICATES AS-1548-1-430 MATERIAL. REFINER TO ENSURE THAT THIS STANDARD MEETS OR EXCEEDS KILLED CARBON STEEL REQUIREMENTS.
- 2) VESSEL TO BE RE-RATED.
- 3) REMOVE ALL INTERNALS AND MODIFY VESSEL AS SHOWN BELOW.
- 4) SEE NOTES F, G AND H ON SHEET 2.

LEGEND:

- NEW OR MODIFIED CONFIGURATION
- - - - - EXISTING CONFIGURATION



* BED MATERIAL, SEE PROJECT SPEC 106.
** INERT CERAMIC BALLS, TYPE I, SEE STD SPEC 3-37.

Drawings Referred to in this Specification

3-331	3-425						
-------	-------	--	--	--	--	--	--

TEC-300-12-Vessel Reference 3-Attachment 1.dgn

ORIGINAL UOP PROJECT NO 6950 (1988)
 *CUSTOMER OR FABRICATION DWG NO & REVISION:
 KOREA HEAVY INDUSTRIES, DWG. NO. K330M38-D-0301, REV 3 (1990)

REV	DATE	BY	CHKD	REV	DATE	BY	CHKD

NOTES:

- MODIFICATIONS REQUIRED FOR THE NEW SERVICE:
- 1) REMOVE EXISTING TRAYS #27-36 AND REPLACE WITH 13 NEW UOP ECMD TRAYS, AS SHOWN. REDUCE TRAY SPACING TO 450 MM. MODIFY TRAY 26 DOWNCOMER LENGTH AND PROVIDE A DISTRIBUTOR TRAP TO SUIT NEW TRAY BELOW.
 - 2) INSTALL NEW 1 INCH ID T1 NOZZLE "GT" ABOVE EXISTING TRAY 39, AS SHOWN.
 - 3) SEE PLAN VIEW FOR ECMD TRAY DOWNCOMER ORIENTATION.
 - 4) FOR EXISTING NOZZLE "N2" AN INTERNAL DISTRIBUTOR IS TO BE FURNISHED BY ECMD TRAY SUPPLIER, SEE UOP PROJECT SPECIFICATION 307.
 - 5) EXISTING MANWAY ORIENTATION AND LOCATION IN THE ECMD TRAYED SECTION OF VESSEL TO BE CONFIRMED BY ECMD TRAY SUPPLIER.
 - 6) SEE NOTES F, G, H AND I ON SHEET 2.

REV

VESSELS
TEC-300-12 ATTACHMENT 1

SERVICE	STABILIZER (EXISTING)	ITEM NO	V-2510
----------------	-----------------------	----------------	--------

Design	INT 0.0 kg/cm2(g)	@000°C
Conditions at Top	EXT 0.0 kg/cm2(g)	@000°C
Operating Conditions	TOP	00°C
	BOTTOM	00°C
Radiograph	*	
Postweld Heat Treat	*	

LEGEND:

- NEW OR MODIFIED CONFIGURATION
- - - - - EXISTING CONFIGURATION

Material	Corrosion Allowance
*	*

This Vessel is in the Following Service(s):

Hydrogen	-
Hydrofluoric (HF) Acid	-
Hydrofluoric (HF) Acid (with Resid. Elem. Control)	-
Wet Hydrogen Sulfide (H2S)	-
Severe Cyclic	-
Caustic	-
Carbonate	-
Amine	-

Vessel Heads

Top	*
Bottom	*

Accessories Applied by Fabricator

Ladder & Platform Clips	*
Insulation Clips & Rings	YES
Vessel Support	*

Nozzles and Manways





Mark	No	Size Inches	Service
	1	6	OUTLET
	1	24	MANWAY
	1	4	INLET
	1	24	MANWAY
N2	1	4	FEED
	1	14	REBOILER RETURN
	1	10	REBOILER DRAW
	1	24	MANWAY
	2	2	LG-LC
	1	3	OUTLET

NEW NOZZLES

GT	1	1 ID	T1
----	---	------	----

Class	ASME CL300 (NEW) EXISTING (*)
Facing	RAISED FACE (NEW) EXISTING (*)

Normal Liquid Level	= 0000 ABOVE BOTTOM TANGENT
Specific Gravity	= 0.00
Delta-P Vessel(Total)	= 0.00 kg/cm2(g)



REMOVE EXISTING TRAY SUPPORT RING(S)
IF NOT UTILIZED FOR THE NEW SERVICE

Drawings Referred to in this Specification

R E V		VESSELS TEC-300-12 ATTACHMENT 1	
SERVICE		DEETHANIZER COLUMN (EXISTING)	
ITEM NO		C-5102	
Design	INT 00.0 kg/cm2(g)	@000°C	(#) BY CONTRACTOR
Conditions at Top	EXT FULL VACUUM	@000°C	(#) THE NUMBER, FLANGE RATING, AND SIZE OF NOZZLES AT THIS LOCATION SHALL BE DETERMINED BY THE CONTRACTOR
Operating Conditions	TOP	00°C	
	BOTTOM	00°C	
Radiograph	MR		
Postweld Heat Treat	MR		
Material	Corrosion Allowance		
KILLED CARBON STEEL	3		
This Vessel is in the Following Service(s):			
Hydrogen	-		
Hydrofluoric (HF) Acid	-		
Hydrofluoric (HF) Acid (with Resid. Elem. Control)	-		
Wet Hydrogen Sulfide (H2S)	-		
Severe Cyclic	-		
Caustic	-		
Carbonate	-		
Amine	-		
Vessel Heads			
Top	2:1 ELLIPTICAL		
Bottom	*		
Accessories Applied by Fabricator			
Ladder & Platform Clips	AS REQUIRED (#)		
Insulation Clips & Rings	YES		
Vessel Support	*		
Nozzles and Manways			
Mark	No	Size Inches	Service
	2	2	LC
	1	22	MANWAY
	4	3/4	LG
	1	1/2	PI
NEW NOZZLE(S)			
AI	1	4	REFLUX
AM	1	24 ID	MANWAY
AD	1	8	OVHD VAPOR
AV	1	2	VENT
AU	(#)	(#)	RELIEF (#) SEE NOTE
BI	1	4	FEED
BM	1	24 ID	MANWAY
CI	1	16	REBOILER RETURN
DC	1	12	BOTTOM OUTLET
Class - ASME CL300 (NEW) * (EXISTING)			
Facing - RAISED FACE (NEW) * (EXISTING)			
Normal Liquid Level = 000 mm ABOVE BOTTOM TANGENT			
Specific Gravity = 0.000			
Delta-P Vessel(Total) = 0.00 kg/cm2			
NOZZLES MUST NOT BE LOCATED IN DOWNCOMERS			

ORIGINAL UOP PROJECT NO 7752 (1979)
* CUSTOMER OR FABRICATION DWG NO & REVISION:
ACERO FABRICANTES C.A. DRAWING NUMBER RCN-150655, REV 5 (1981)



NOTES:

MODIFICATIONS REQUIRED FOR THE NEW SERVICE:

- 1) REMOVE ALL EXISTING TRAYS AND REPLACE WITH 40 TOTAL NEW TRAYS, AS SHOWN. SEE UOP PROJECT SPECIFICATION 307.
- 2) REPLACE EXISTING TOP HEAD, UPPER 900 ID SHELL PORTION AND CONE SECTION ABOVE TRAY 21 WITH A NEW 1700 ID SHELL AND TOP HEAD AS SHOWN TO MATCH LOWER SHELL PORTION.
- 3) REPLACE EXISTING 8 INCH BOTTOM OUTLET NOZZLE "DC" AND VORTEX BREAKER WITH A NEW 12 INCH NOZZLE AND NEW VORTEX BREAKER AS SHOWN.
- 4) REPLACE EXISTING REBOILER VAPOUR RETURN NOZZLE "CD" WITH NEW 16 INCH NOZZLE "CI".
- 5) SEE NOTES F, G AND H ON SHEET 2.

LEGEND:

- NEW OR MODIFIED CONFIGURATION
- - - - - EXISTING CONFIGURATION



REMOVE EXISTING TRAY SUPPORT RING(S) IF NOT UTILIZED FOR THE NEW SERVICE

Drawings Referred to in this Specification

3-115	3-116	3-117	3-118	3-119	3-120	3-121	3-122
-------	-------	-------	-------	-------	-------	-------	-------